



ISO 15693 CF Reader/Writer



The ISO 15693 Compact Flash (CF) Reader has been designed and developed to allow PDAs and Pocket PC devices to access smart labels and cards which comply with the ISO15693 standard (ISO18000-3).

The CF Reader module can work with any of the most recent Pocket PC PDAs which provide a CF II interface. A full SDK with drivers and sample applications is available.

The ISO 15693 CF Reader is suitable for :

- Logistics
- Transportation
- Ticketing
- Identification
- Asset Tracking

Product specifications:

Dimensions: 62 x 43 x 6.5mm

Weight: 17g

Material: PBT and ABS

Operating distance : Up to 6cm (depends on transponders)

Power supply 3.3 V

Power Consumption Active: 100mA

Power Consumption Stand-by: 15mA

User interface: Dual color LED indicator

Operating system: Windows CE and Windows Mobile 5

Temperature range : 0°C to 50°C

Supported transponders: ISO 15693, Tag-it and I-CODE 1

ISO: ISO 15693

Option: External antenna for longer read range possible upon request

Order number: ACC-CF-15693

:

ACC Systems Inc. 1 Robert Lane, Glen Head, NY 11545 ph. 516-674-0191

Email: rfid@accsystemsinc.com web: www.accsystemsinc.com