

AT980

Wine & Liquor Tracking, Shopping mall,
Mobile Payment Service etc.



ACCESSORIES



SPECIFICATION

Performance Characteristics

Processor	Marvell™ PXA 320 806MHz
Operating System	Windows CE 5.0 / Windows Embedded handheld 6.5
Memory	256MB (512MB*) RAM / 512MB (1GB*) ROM
Display	3.5" QVGA with Backlight, TFT LCD, 240x320 Pixel, 262, 144 Color (VGA*)
Weight	520g (PDA only, without battery)
Operating Temp.	-20 ℃ ~ 60 ℃
Storage Temp.	-30 ℃ ~ 70 ℃
Humidity	95% non-condensing
Drop Spec.	1.5M Drop to concrete
Dust & Water Proof	IP65

Physical Characteristics

Audio	Phone Receiver, Speaker, Ear Jack, Microphone
Standard I/O Port	USB 1.1 Client / USB Host & Serial (RS-232) via gender cable or Cradle
Expansion Slot	1Micro SD Slot (SDHC), 1SIM Slot, 3SAM Slots
Notification	Vibrator and LED, Speaker
Dimensions(L x W x H)	221 x 82 x 33.7 (54.6)mm

Battery Supply

Main Battery	Lithium-Ion Polymer 3.7V 2,000mAh (Rechargeable)
Backup Battery	Lithium-Ion Polymer 3.7V 80mAh (Rechargeable)
Power Adapter	Input AC110V ~ 240V / Output DC 5V 3A

Network Characteristics

WLAN	IEEE 802.11 b/g/a Compliant
Bluetooth	Class II, v2.1 + EDR
Radio	MODEM 3G (GSM / GPRS / HSDPA / HSPA+)
GPS	Internal Antenna

Data Capture Device

Barcode Engine	1D Laser or 2D Imager Barcode Scanner
Printer	2" Thermal Printer/MSR/Smart Card Reader
Camera	3.0 Mega Pixel Auto Focus with Flash
Finger Print	Finger Printer Scanner

UHF 900 Mhz Reader/Writer

Frequency	860MHz~960MHz
Reading range	0M ~ 7M (According to Tag & Environment)
Writing range	0M ~ 3M (According to Tag & Environment)
RF output	1W EIRP
Protocol	GEN2, ISO/IEC 18000-6C, 18000-6B*
Special function	Anti-Collision

HF 13.56Mhz Reader/Writer

Applied RFID Tag	ISO15693, MIFARE, ISO14443 A/B*
Reading range	Based On Tag : 0 ~ 10Cm

Cradle

Standard Interface	USB 1.1 Host / USB Client / DC Power Jack / Extra Battery Charger / 9pin RS232 Interface
Ethernet Interface	RJ-45 Ethernet Interface*



* All Features and specifications described are subject to change without notice.